

TECHNICAL INFORMATION

Amberizer



WS Amberizer is an additive to achieve the traditional look of an aged oil modified polyurethane finish with waterborne coatings.

- Adds the look of oil based finish
- Great to touch up and repair of old floors
- Convenient package and great color consistency


Recommended use:

Suitable for all LOBADUR® waterborne finishes.

Technical Data

Art.-no.
11540

Item-#:
LO-FI-001



Storage and transportation

Shelf life: 36 months in unopened containers. Store and transport between 41°F to 77°F.
KEEP FROM FREEZING.

US Regulatory VOC

< 2 g/l

Application

- For professional Use only!
- BEFORE USING, READ AND UNDERSTAND ALL DIRECTIONS AND MATERIAL SAFETY DATA SHEETS.
- For technical advice call our LOBA-WAKOL Technical Service at 1-800.230.6456.
- Sand and prepare floors according to NWFA instructions.
- ALWAYS PREPARE A SAMPLE OR TEST AREA TO DETERMINE COMPATIBILITY, APPEARANCE AND DESIRED RESULTS.
- Shake material well before use.
- Do not thin. Do not add water.
- Do not apply at temperatures below 55°F. Make sure material is at room temperature. Always maintain adequate ventilation during all phases of the coating and drying process.
- Apply evenly at the recommended coverage rate. Avoid streaks and puddles and lap marks.

Drying time

- WS Amberizer does not alter the dry time of the desired finish.

9/2018



TECHNICAL INFORMATION

Amberizer



Application

Mixing ratio

Added amount 2%. One bottle to one gallon.

Recommended Procedure for wood floors:

- Add WS Amberizer only right before the application by shaking or stirring thoroughly. When using 2-component-systems (WS 2K Supra, 2K Supra^{A.T.}) add WS Amberizer only AFTER adding hardener to the mass!
- Perform application according to technical information of the finish, regard pro-longed drying times.

Compatibility

When this product is used in combination with other LOBA products also the Technical Information of these products has to be followed. Always prepare test areas to determine suitability of other products than LOBA.

9/2018



TECHNICAL INFORMATION

Amberizer



General guidelines

Cleaning of tools: Clean tools and equipment immediately with water.

Cure Time: The stated drying and cure times are based on ideal conditions (68°F, 65% rH) at the recommended application rates. Recommended conditions are 50°F-77°F/40-75%rH). Insufficient ventilation, high humidity, lower temperatures, increased coat thickness can prolong the curing process considerably. The floor can be lightly used 24 hours after application, but is still susceptible to scuffing or marring at this time. Full curing is achieved after 5 days. Do not use safety covers on floor, do not replace carpets or rugs and also do not clean floors with a damp cloth before the final hardness has been reached.

Safety Precautions: Even when working with low-emission products the usual safety measures must be taken. Keep away from children. Do not eat, drink or smoke in working areas. Wear suitable safety gloves. Make sure working areas are ventilated sufficiently. Clean left-overs off of hands. Change soiled clothes. Ventilate working rooms during working and drying time avoiding draft.

First Aid: If swallowed, do not induce vomiting. Call for medical help immediately. Never give anything by mouth to an unconscious person. If inhaled, remove to fresh air. If breathing is difficult or other respiratory complaints, get medical attention. In case of contact, immediately flush eyes or skin with plenty of water. Do not use solvents or thinners. Remove contaminated clothing or shoes. For eye contact, rinse opened eye for several minutes under running water. Call a physician if irritation occurs.

WARNING! If you scrape, sand or remove old paint from wooden floors, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Special Information The information in this document and any other information or advice we provide is intended for our customers only, and all information and advice is subject to the terms and limitations in Loba-Wakol's General Terms and Conditions, including without limit its limited warranty ("Terms"). The Terms are not expanded, changed or waived by the information in this document or by any information or advice given by Loba-Wakol. Loba-Wakol has no relationship or obligation to anyone other than the customer that originally purchases the product from Loba-Wakol.

The information in this document and any other information or advice we provide is the result of our prior experience and our knowledge of our products. Due to the wide variety of application possibilities and processing conditions, it is the customer's responsibility to test our product for suitability for its intended purpose. When in doubt, call our Technical Service for support. Technical Information is also available by visiting our website www.loba-wakol.com. You must read and understand, and have your professional installer read and understand, all information contained in our Terms and in our published specifications, technical data sheets, written directions for installation, use and maintenance, and labels on the product. If you have any questions during application or use, immediately stop the application and use and contact our Technical Service. For information about other products offered by Loba-Wakol, please check the technical information concerning those products.

The words or symbols denoted by ® stand for trademark rights that are at least registered and protected in the territory of Germany.

9/2018

